




Radial Arm Saw

BS-999



Description

 <p>BS-999 Radial arm saw 45°/90°</p>	<p>Cut with piloting arm at 45° to the fence. Pivoting arm adjustment : 45° on the left-45° on the right</p>
	<p>Cut with 45° - tilted saw blade. Saw blade adjustment : 0 - 90° Note : front lifting of the piloting arm (upon request)</p>
	<p>Cut with saw blade perpendicular and square to the fence; cutting off</p>
	<p>Cut with saw blade parallel to the fence for squaring and trimming operations</p>
	<p>Cut or milling with saw blade in horizontal position and parallel to the fence</p>



Saw holder saddle with 8 ball bearings and interchangeable ways with added material (15 mm)



Returning-type spring



Infrared laser equipment

Specification

Motor	4.5HP / 3PH
Motor speed	2900 RPM
Bearings for rails	Linear bearing / 8pcs
Spindle bore	Ø 1" (25.4mm) or 30mm
Blade diameter	20" (508 mm) (sawblade is excluded)
Thickness of cut	20" (155mm)
Head swiveling	0~180°
Head tilting	0~90°
Max. trimming width	1140 mm
Max cross cutting length	18"
Table area L x W	820 x 1140 mm
Machine size	1450 x 1250 x 1600 mm
Packing size	1480 x 1070 x 790 mm
N.W. / G.W.	250/290 kgs

***We reserve the right to amend any of the above specifications without prior notice.**

Standard Equipment

1. Brake Motor
2. Safety Switch Box
3. Infrared Device
4. Rear Dust Collection Cover
5. Return Spring
6. Safety Guard Interlock Plug-in Switch
7. Motor Auto Home-Position Locking Device

SK Global Co., Ltd.

No. 172, Hsin Yi Street., Feng Yuan Dist., Taichung 420003, TAIWAN

T +886-4-25121980 **F** +886-4-25122703

E info@skglobal.com.tw

www.skglobal.com.tw