UNISUNX CNC formatrundsav type SMV8D

Type S er med hurtigstop HAND GUARD der sænker og stopper savklingen på 0,25 sekunder (et kvart sekund), før hånden når klingen.
Kan leveres både til XPD og XP modellerne



XPD automatisk klapstop – SP manuel klapstop

- Crosscut guide fence by servo motor control XPD model
- Motorizing up/down for main saw and scoring saw
- Electrical tilting for 45 degree
- Electrical rip fence
- Type A protection hood
- LEUCO saw blade
- European sliding table
- PC control with optimization software
- Maximum main saw blade diameter 400mm
- Pressure unit

Tekniske Data:

Dimension of slidng table	3200×435mm
Gross cut capacity	3200mm
Width of cut between saw blade and rip fence	1300mm
Main saw blade diameter	φ300mm(φ250-φ400)

PE Maskiner Silkeborg
www.pemaskiner.dk
mail@pemaskiner.dk
Telefon: +45 86870535

UNISUNX CNC formatrundsav type SMV8D

Type S er med hurtigstop HAND GUARD der sænker og stopper savklingen på 0,25 sekunder (et kvart sekund), før hånden når klingen.
Kan leveres både til XPD og XP modellerne

Scoring saw blade diameter	φ120mm
Height of cut with saw blade φ300mm at 90°	80mm
Height of cut with saw blade φ300mm at 45°	φ55mm
Speed of main saw spindle	3000/4000/5000rpm
Speed of scoring saw blade	8000r/min
Main spindle diameter	φ30mm
Scoring spindle diameter	φ20mm
Tilting saw blade	0-45° by servo motor control
Main motor	5.5KW
Scoring motor	0.75kw
Net weight	1080kg

PE Maskiner Silkeborg
www.pemaskiner.dk
mail@pemaskiner.dk
Telefon: +45 86870535